



INQUIRY

ORDER

Sautter Lift Components

GmbH

Remsstrasse 2

70806 Kornwestheim, Germany

Phone: +49 – (0) 7154 – 9996-0

Fax: +49 – (0) 7154 – 9996-501

Email: sales@slc-liftco.com

Order no.:

Customer:

Delivery address:

Cust. order no:

Contact Person:

Site reference:

Date:

Comm. no.:

Required date:

PROGRESSIVE SAFETY GEAR BF

Quantity:

Braking downwards:

Braking up-/downwards:

Braking only upwards:

Miscellaneous:

BF1D- _____

BF2D- _____

BF3D-2

By means of the technical data we select the correct type of safety gear for you.

Please specify additional components. For special requests please use the field „Miscellaneous“.

1. Technical Data

Rated speed VN: _____ m/s

Rated load Q: _____ kg

Car weight P: _____ kg (incl. Sling weight)

Compens. rope weight CR: _____ kg

Mass counterweight CTW _____ kg

Rail head thickness:

9mm

16mm

____ mm (> 9 and <16 mm)

Production method rail:

machined

cold drawn

Mounting at lower traverse

Surface of the guide rail:

oiled

dry

Mounting at upper traverse

Roller switch

without locking

with locking

Cable loop

5m

8m

2. Traction sheave (These details are only necessary for braking in upwards direction)

Diameter traction sheave _____ mm

Suspension: _____ :1

Inertia of traction sheave side (Traction sheave + drive): _____ kgm²

Notice: If the indication of inertia is missing, Sautter Lift Components applies a standard figure based on experience in braking force calculation for braking in upward direction. Possibly an adjustment of the braking force is required.

3. Options and additional components

Roller switch with 2 NC / 2 NO contacts (4-wire cable)

EX-type roller switch

Safety gear shaft, straight Safety gear shaft, cranked

Distance between gauge _____ mm (from 1600 mm reinforced shaft)

Retrofit Schindler SG: T1BR GK1 RF-1 T3BR T5BR

Retrofit Haushahn SG: RFII ZFII

without outer housing: with standard bolts Long bolt without bolts

Tripping device (refer to form FB 8.2.2.1 02)

Adapter plate or changed bore hole pattern (refer to form FB 8.2.2.1 09)

PU accessory pull tube, rope 6.5

PU accessory pull tube, rope 8.0

Pull tube 3,000 mm

Pull tube 1,000 mm

PU guide shoes (2 pieces)

PU lubricator

Fastening material